



## COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

| MODEL DATA - FOR COMPRESSED AIR |   |                                       |                                |   |
|---------------------------------|---|---------------------------------------|--------------------------------|---|
| 1                               | Manufacturer: <b>Kaishan Compressor USA</b>   |                                       |                                |   |
| 2                               | Model Number: <b>KRSP2-30-100 VSD</b>   |                                       | Date:                          | <b>02/07/21</b>                           |
|                                 | <input checked="" type="checkbox"/> Air-cooled  | <input type="checkbox"/> Water-cooled | Type:                          | <b>Screw</b>                              |
|                                 |   |                                       |                                | # of Stages: <b>2</b>                     |
| 3*                              | Full Load Operating Pressure <sup>b</sup>   | <b>100</b>                            | psig <sup>b</sup>              |   |
| 4                               | Drive Motor Nominal Rating  | <b>30</b>                             | hp                             |   |
| 5                               | Drive Motor Nominal Efficiency  | <b>96.0</b>                           | percent                        |   |
| 6                               | Fan Motor Nominal Rating (if applicable)  | <b>1</b>                              | hp                             |   |
| 7                               | Fan Motor Nominal Efficiency  | <b>83.9</b>                           | percent                        |   |
| 8*                              | Input Power (kW)  |                                       | Capacity (acfm) <sup>a,d</sup> | Specific Power (kW/100 acfm) <sup>d</sup> |
|                                 | 29.5  |                                       | <b>162</b>                     | <b>18.21</b>                              |
|                                 | 21.2  |                                       | <b>113</b>                     | <b>18.76</b>                              |
|                                 | 15.9  |                                       | <b>81</b>                      | <b>19.63</b>                              |
|                                 | 13.0  |                                       | <b>65</b>                      | <b>20.00</b>                              |
| 8.9                             |   | <b>41</b>                             | <b>21.71</b>                   |   |
| 9*                              | Total Package Input Power at Zero Flow <sup>c, d</sup>  |                                       | <b>0.0</b>                     | <b>kW</b>                                 |
| 10                              | Isentropic Efficiency   |                                       | <b>70.30</b>                   | <b>%</b>                                  |
| 11                              | <p style="text-align: center; font-size: small;"> <b>Note: Graph is only a visual representation of the data in Section 8</b><br/>           Note: Y-Axis Scale, 10 to 35, +5kW/100acfm increments if necessary above 35<br/>           X-Axis Scale, 0 to 25% over maximum capacity         </p> |                                       |                                |   |

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: [www.cagi.org](http://www.cagi.org)



Member

- NOTES:
- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
  - The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
  - No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
  - Tolerance is specified in ISO 1217, Annex E, as shown in table below:  
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

| Volume Flow Rate at specified conditions |                       | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m <sup>3</sup> / min                     | ft <sup>3</sup> / min | %                | %                           | %                         |
| Below 0.5                                | Below 17.6            | +/- 7            | +/- 8                       |                           |
| 0.5 to 1.5                               | 17.6 to 53            | +/- 6            | +/- 7                       | +/- 10%                   |
| 1.5 to 15                                | 53 to 529.7           | +/- 5            | +/- 6                       |                           |
| Above 15                                 | Above 529.7           | +/- 4            | +/- 5                       |                           |

ROT 031.1